

Aktua ux+

Tip proces fabricatie 5/64" fir tuns

Clasa de trafic EN 1307
31

Tip material/compozitie 100% nylon imprel IMPREL

Rezi. la scaunul cu rotile EN 985
A: intensive use

Suport principal ultratex quick+

Metoda de instalare Stretched
Release bond

Greutate fir Ca. 580 gr/m²

Rezistenta termica ISO 8302
0.13 m² K/W

Greutate totala Ca. 1.590 gr/m²

Rezistenta culorii la lumina ISO 105-B02
≥ 5-6

Inaltime fir Ca. 5 mm

Rezistenta culorii la apa EN ISO 105-E01
≥ 4-5

Inaltime totala Ca. 8 mm

Rezistenta la foc EN 13501-1
Cfl-s1

Densitate crosetare Ca. 307 000/m²



Onder voorbehoud van wijzingen van de technische specificaties - Sous-éser e de modifications echniques - Unter Vorbehalt von technischen Änderungen - All rights reserved to alter technical specification

Aktua	87	93	97	110	116	127	143	144	178	194
ULTRATEX QUICK+ CA 4M	○	○	○	○	○	○	○	○	○	○
ULTRATEX QUICK+ CA 5M	○	○	○	○	○	○	○	○	○	○

