

565 Soil Guard™



- High traction mat made to withstand the toughest conditions due to its superior rubber compound.
- Stops dirt, grit and grime outside the doorway.
- Bevelled edges for safety and easy cart access.
- Non shifting grip pattern underneath.
- Outdoor entrances - Heavy foot traffic area.
- Hose off with water and hang to dry.



565 Soil Guard™

PRODUCT SPECIFICATIONS			
Designation	Dust Control Matting		
Type	Non-absorbent / scrape rubber mat		
Description	High traction mat, bevelled edges, non shifting grip pattern underneath.		
Material	Natural rubber compound		
Process	Compression moulding		
Category	Outdoor Non-absorbent - Rubber classics		
Recommended use	Outdoor - heavy foot traffic areas		
Colours	Black		
Weight	7,5 kg/m²		
Thickness	7 mm		
Standard sizes	90 cm x 150 cm		
Custom sizes			
Special remarks			
PRODUCT TESTING			
Tests		Norms	Results
Abrasion resistance		ASTM D3884	3.30% weight loss
Colour fastness to light		AATCC 16E	
Accelerated wear test by sim floor machine		U.S.	
Accelerated soiling		U.S.	
Anti-slip		DIN51130 BGR181	
Water retention		U.S	
Hardness		U.S	
Coefficient of friction		ASTM C1028-96	0,78
FIRE TESTING			
	Surface Flammability	ASTM D2859	Pass
	Classification of the reaction to fire performance	DIN EN 13501-1	
Sustainability		<ul style="list-style-type: none">• Recyclable material• REACH compliant (Registration, Evaluation, Authorization and restrictions of Chemicals)• Contributes to cleaner environment by reducing need of cleaning chemicals	